

# 1MBC10-060, 1MBC10D-060, 1MBG10D-060

Molded IGBT

## 600V / 10A


## Molded Package

### ■ Features

- Small molded package
- Low power loss
- Soft switching with low switching surge and noise
- High reliability, high ruggedness (RBSOA, SCSOA etc.)
- Comprehensive line-up

### ■ Applications

- Inverter for Motor drive
- AC and DC Servo drive amplifier
- Uninterruptible power supply



### ■ Maximum ratings and characteristics

- Absolute maximum ratings (at  $T_c=25^\circ\text{C}$  unless otherwise specified)



#### 1MBC05-060 / IGBT

Item	Symbol	Rating	Unit		
Collector-Emitter voltage	$V_{CES}$	600	V		
Gate-Emitter voltage	$V_{GES}$	$\pm 20$	V		
Collector current	DC	$T_c=25^\circ\text{C}$	$I_{C25}$	20	A
		$T_c=100^\circ\text{C}$	$I_{C100}$	10	A
	1ms	$T_c=25^\circ\text{C}$	$I_{cp}$	80	A
Max. power dissipation(IGBT)	$P_c$	75	W		
Operating temperature	$T_j$	+150	$^\circ\text{C}$		
Storage temperature	$T_{stg}$	-40 to +150	$^\circ\text{C}$		
Screw torque	-	40	N·m		

#### 1MBC05D-060, 1MBG05D-060 / IGBT+FWD

Item	Symbol	Rating	Unit		
Collector-Emitter voltage	$V_{CES}$	600	V		
Gate-Emitter voltage	$V_{GES}$	$\pm 20$	V		
Collector current	DC	$T_c=25^\circ\text{C}$	$I_{C25}$	20	A
		$T_c=100^\circ\text{C}$	$I_{C100}$	10	A
	1ms	$T_c=25^\circ\text{C}$	$I_{cp}$	80	A
Max. power dissipation (IGBT)	$P_c$	75	W		
Max. power dissipation (FWD)	$P_c$	35	W		
Operating temperature	$T_j$	+150	$^\circ\text{C}$		
Storage temperature	$T_{stg}$	-40 to +150	$^\circ\text{C}$		
Screw torque	-	40	N·m		

### ■ Equivalent Circuit Schematic



● Electrical characteristics (at Tj=25°C unless otherwise specified)

1MBC10-060 / IGBT

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Zero gate voltage collector current	ICES	–	–	1.0	VGE=0V, VCE=600V	mA
Gate-Emitter leakage current	IGES	–	–	20	VCE=0V, VGE=±20V	µA
Gate-Emitter threshold voltage	VGE(th)	5.5	–	8.5	VCE=20V, Ic=10mA	V
Collector-Emitter saturation voltage	VCE(sat)	–	–	3.0	VGE=15V, Ic=10A	V
Input capacitance	Cies	–	700	–	VGE=0V	pF
Output capacitance	Coes	–	150	–	VCE=10V	
Reverse transfer capacitance	Cres	–	20	–	f=1MHz	
Turn-on time	ton	–	–	1.2	VCC=300V Ic=10A	µs
	tr	–	–	0.6	VGE=±15V	
Turn-off time	toff	–	–	1.0	RG=220 ohm	µs
	tf	–	–	0.35	(Half Bridge)	

1MBC10D-060, 1MBG10D-060 / IGBT+FWD

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Zero gate voltage collector current	ICES	–	–	1.0	VGE=0V, VCE=600V	mA
Gate-Emitter leakage current	IGES	–	–	20	VCE=0V, VGE=±20V	µA
Gate-Emitter threshold voltage	VGE(th)	5.5	–	8.5	VCE=20V, Ic=10mA	V
Collector-Emitter saturation voltage	VCE(sat)	–	–	3.0	VGE=15V, Ic=10A	V
Input capacitance	Cies	–	700	–	VGE=0V	pF
Output capacitance	Coes	–	150	–	VCE=10V	
Reverse transfer capacitance	Cres	–	20	–	f=1MHz	
Turn-on time	ton	–	–	1.2	VCC=300V, Ic=10A	µs
	tr	–	–	0.6	VGE=±15V	
Turn-off time	toff	–	–	1.0	RG=220 ohm	µs
	tf	–	–	0.35	(Half Bridge)	
FWD forward on voltage	VF	–	–	3.0	IF=10A, VGE=0V	V
Reverse recovery time	trr	–	–	0.3	IF=10A, VGE=-10V, di/dt=100A/µs	µs

● Thermal resistance characteristics

1MBC10-060 / IGBT

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Thermal resistance	Rth(j-c)	–	–	1.66	IGBT	°C/W


1MBC10D-060, 1MBG10D-060 / IGBT+FWD

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Thermal resistance	Rth(j-c)	–	–	1.66	IGBT	°C/W
	Rth(j-c)	–	–	3.57	FWD	°C/W

■ Outline drawings, mm


1MBC10-060, 1MBC10D-060

TO-110AB



1MBG10D-060

T pack-S (SMD type)




Characteristics

1MBC10-060, 1MBC10D-060, 1MBG10D-060


Collector current vs. Collector-Emitter voltage

Tj=25°C




Collector current vs. Collector-Emitter voltage

Tj=125°C




Collector-Emitter vs. Gate-Emitter voltage

Tj=25°C




Collector-Emitter vs. Gate-Emitter voltage

Tj=125°C




Switching time vs. Collector current

Vcc=300V, Rg=220 ohm, VGE=±15V, Tj=25°C









Switching time vs. Collector current

Vcc=300V, Rg=220 ohm, VGE=±15V, Tj=125°C



Characteristics


1MBC10-060, 1MBC10D-060, 1MBG10D-060



■ Characteristics


1MBC10-060,1MBC10D-060,1MBG10D-060

Transient thermal resistance




1MBC10D-060,1MBG10D-060


Reverse recovery time vs. Forward current



Reverse recovery current vs. Forward current



Forward current vs. Forward voltage



Reverse recovery time characteristics vs. -di/dt

