

PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

MITSUBISHI IGBT MODULES
CM10AD05-24H
 MEDIUM POWER SWITCHING USE
 FLAT BASE, INSULATED TYPE


CM10AD05-24H



- IC 10A
- VCES 1200V
- Insulated Type
- 3φ Inverter + 3φ Converter + Brake + Thermistor

APPLICATION

AC & DC motor controls, General purpose inverters



PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

CM10AD05-24H

**MEDIUM POWER SWITCHING USE
 FLAT BASE, INSULATED TYPE**

MAXIMUM RATINGS (T_j = 25°C)

INVERTER PART

Symbol	Parameter	Conditions	Rating	Unit
V _{CES}	Collector-emitter voltage	G-E Short	1200	V
V _{GES}	Gate-emitter voltage	C-E Short	±20	V
I _C	Collector Current	T _c = 25°C	10	A
I _{CM}		PULSE (Note. 2)	20	
I _E (Note.1)	Emitter Current	T _c = 25°C	10	A
I _{EM} (Note.1)		PULSE (Note. 2)	20	
P _C (Note.3)	Maximum collector dissipation	T _c = 25°C	62	W

BRAKE PART

Symbol	Parameter	Conditions	Rating	Unit
V _{CES}	Collector-emitter voltage	G-E Short	1200	V
V _{GES}	Gate-emitter voltage	C-E Short	±20	V
I _C	Collector Current	T _c = 25°C	10	A
I _{CM}		PULSE (Note. 2)	20	
P _C (Note.3)	Maximum collector dissipation	T _c = 25°C	62	W
V _{RRM}	Repetitive peak reverse voltage	Clamp diode part	1200	V
I _{FM} (Note.3)	Forward current	Clamp diode part	10	A

CONVERTER PART

Symbol	Parameter	Conditions	Rating	Unit
V _{RRM}	Repetitive peak reverse voltage		1600	V
E _a	Recommended AC input voltage		440	V
I _O	DC output current	3φ rectifying circuit	10	A
I _{FSM}	Surge (non-repetitive) forward current	1/2 cycle at 60Hz, peak value, Non-repetitive	100	A
I ² t	I ² t for fusing	Value for one cycle of surge current	42	A ² s

COMMON RATING

Symbol	Parameter	Conditions	Rating	Unit
T _j	Junction temperature		-40 ~ +150	°C
T _{stg}	Storage temperature		-40 ~ +125	°C
V _{iso}	Isolation voltage	AC 1 min.	2500	V
—	Mounting torque	Mounting M4 screw	1.47 ~ 1.96	N·m
—	Weight	Typical value	120	g

PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

CM10AD05-24H

**MEDIUM POWER SWITCHING USE
 FLAT BASE, INSULATED TYPE**

**ELECTRICAL CHARACTERISTICS (T_j = 25°C)
 INVERTER PART**

Symbol	Parameter	Test conditions	Limits			Unit		
			Min.	Typ.	Max.			
ICES	Collector cutoff current	VCE = VCES, VGE = 0V	—	—	1	mA		
VGE(th)	Gate-emitter threshold voltage	IC = 1.0mA, VCE = 10V	4.5	6	7.5	V		
IGES	Gate-emitter cutoff current	VGE = VGES, VCE = 0V	—	—	0.5	μA		
VCE(sat)	Collector-emitter saturation voltage	T _j = 25°C T _j = 150°C	IC = 10A, VGE = 15V	(Note.4)	—	2.7	3.4	V
					—	2.45	—	
Cies	Input capacitance	VCE = 10V VGE = 0V	—	—	2.0	nF		
Coes	Output capacitance		—	—	1.5			
Cres	Reverse transfer capacitance		—	—	0.4			
QG	Total gate charge	VCC = 600V, IC = 10A, VGE = 15V	—	50	—	nC		
td (on)	Turn-on delay time	VCC = 600V, IC = 10A VGE1 = VGE2 = 15V RG = 31Ω Resistive load	—	—	100	ns		
tr	Turn-on rise time		—	—	200			
td (off)	Turn-off delay time		—	—	150			
tf	Turn-off fall time		—	—	350			
VEC(Note.1)	Emitter-collector voltage	IE = 10A, VGE = 0V	—	—	3.5	V		
trr (Note.1)	Reverse recovery time	IE = 10A, VGE = 0V	—	—	250	ns		
Qrr (Note.1)	Reverse recovery charge	die / dt = - 20A / μs	—	0.08	—	μC		
Rth(j-c)Q	Thermal resistance	IGBT part, Per 1/6 module	—	—	2.0	°C/W		
Rth(j-c)R		FWDi part, Per 1/6 module	—	—	3.1			

BRAKE PART

Symbol	Parameter	Test conditions	Limits			Unit		
			Min.	Typ.	Max.			
ICES	Collector cutoff current	VCE = VCES, VGE = 0V	—	—	1	mA		
VGE(th)	Gate-emitter threshold voltage	IC = 1.0mA, VCE = 10V	4.5	6	7.5	V		
IGES	Gate-emitter cutoff current	VGE = VGES, VCE = 0V	—	—	0.5	μA		
VCE(sat)	Collector-emitter saturation voltage	T _j = 25°C T _j = 150°C	IC = 10A, VGE = 15V	(Note.4)	—	2.7	3.4	V
					—	2.45	—	
Cies	Input capacitance	VCE = 10V VGE = 0V	—	—	2.0	nF		
Coes	Output capacitance		—	—	1.5			
Cres	Reverse transfer capacitance		—	—	0.4			
QG	Total gate charge	VCC = 600V, IC = 10A, VGE = 15V	—	50	—	nC		
VFM	Forward voltage drop	IF = 10A, Clamp diode part	—	—	1.7	V		
Rth(j-c)Q	Thermal resistance	IGBT part	—	—	2.0	°C/W		
Rth(j-c)R		Clamp diode part	—	—	3.1			

CONVERTER PART

Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
IRRM	Repetitive reverse current	VR = VRRM, T _j = 150°C	—	—	8	mA
VFM	Forward voltage drop	IF = 10A	—	—	1.7	V
Rth(j-c)	Thermal resistance	Per 1/6 module	—	—	2.4	°C/W

