



M I C R O T U N E®

RF SILICON AND SUBSYSTEMS SOLUTIONS
FOR BROADBAND COMMUNICATIONS AND AUTOMOTIVE ELECTRONICS

MT5001 VIDEOCASTER™ PRODUCT BRIEF

The MT5001 VideoCaster is a four-channel Video on Demand upconverter designed to reduce space, power and cost.



MT5001 VideoCaster Module

The MT5001 VideoCaster™ subsystem is a high quality frequency agile upconverter designed specifically for video on demand systems. The RF subsystem converts a QAM modulated signal centered at an intermediate frequency of 36.125 MHz or 44.00 MHz to any frequency between 50 MHz and 860 MHz at a user selectable output level between 50 dBmV and 61 dBmV. Based on a proprietary Microtune chipset, the module provides the highest upconverter density in the market packing four independent upconverters into a 98.1mm x 88.4mm x 14.1mm module. The MT5001 VideoCaster also features the lowest available power dissipation at 6.5W per channel.

APPLICATIONS

- Video on demand (VOD)

FEATURES

- Smallest upconverter available
- Lowest power per channel upconverter available
- Lowest cost per channel upconverter available
- Operates with 36.125 MHz or 44.00 MHz IF inputs
- Meets requirements for interactive video on demand applications
- Fully programmable via 2-wire serial interface
- When integrated into headend equipment eliminates the need for separate racks of upconverters
- 50 MHz to 860 MHz output programmable in 12.5 kHz steps
- Output power adjustable from 50 dBmV to 61 dBmV in 0.1 dB steps
- Built-in power detectors allow independent monitoring of each output level
- Built-in fault detection ensures robust system operation

M I C R O T U N E

MT5001 VIDEOCASTER™

PRODUCT BRIEF

OPERATING CHARACTERISTICS

PARAMETER	MIN	TYP	MAX	UNIT
Power supply voltage	5.8	6	6.2	V
Power from supply		26		W
Ambient operating temperature	0		50	°C
Airflow over module	150	200		LFPM
ESD protection, human body model	2000			V
2-wire serial bus input voltage			3.3	V

ABSOLUTE MAXIMUM RATINGS

PARAMETER	MIN	TYP	MAX	UNIT
Supply voltage			7	V
Storage temperature range	-40		+70	°C

SPECIFICATIONS

PARAMETER	MIN	TYP	MAX	UNIT
Input frequency		44.00		MHz
Alternate input frequency		36.125		MHz
Input impedance		75		Ω
Output frequency	50		860	MHz
Output impedance		75		Ω
Output level	50		61	dBmV
Frequency step size	12.5			kHz

MECHANICAL CHARACTERISTICS

CHARACTERISTIC	DESCRIPTION
Dimensions	114.5 x 105.9 x 14.1 mm
Weight	200g
Connector 20-pin pinheader	Samtec ASP31714-04
Suggested receptacle for 20-pin pinheader	Samtec SMM-110-01-S-D-P-TR (20-pin)
Connector 4-pin pinheader	Samtec ASP31714-03
Suggested receptacle for 4-pin pinheader	Samtec SMM-102-01-S-D-P-TR (4-pin)
F-connector mechanical specification	The F-connector is according IPS-SP-406 and IEC 169-24



Microtune, Inc., 2201 Tenth Street, Plano, TX 75074, USA

Tel: +1-972-673-1600, Fax: +1-972-673-1602, E-mail: sales@microtune.com, Web site: www.microtune.com

For a detailed list of design centers, sales offices, and sales representatives, visit our Web site at www.microtune.com.

The information in this document is believed to be accurate and reliable. Microtune assumes no responsibility for any consequences arising from the use of this information, nor from any infringement of patents or the rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or other rights of Microtune. The information in this publication replaces and supersedes all information previously supplied, and is subject to change without notice. The customer is responsible for assuring that proper design and operating safeguards are observed to minimize inherent and procedural hazards. Microtune assumes no responsibility for applications assistance or customer product design.

The devices described in this document are not authorized for use in medical, life-support equipment, or any other application involving a potential risk of severe property or environmental damage, personal injury, or death without prior express written approval of Microtune. Any such use is understood to be entirely at the user's risk.

Microtune is a registered trademark of Microtune, Inc. MicroTuner, MicroStreamer, VideoCaster, DataCaster, and the Microtune logo are trademarks of Microtune, Inc. All other trademarks belong to their respective companies.

Microtune's products are protected by one or more of the following U.S. patents: 5,625,325; 5,648,744; 5,717,730; 5,737,035; 5,739,730; 5,847,612; 6,100,761; 6,104,242; 6,163,684; 6,169,569; 6,172,378; 6,177,964; 6,211,745; 6,218,899; 6,268,778; 6,310,387; 6,323,736; 6,355,537; 6,429,502; 6,535,068; 6,580,313; 6,608,522; 6,631,257; 6,714,776; 6,725,463; 6,744,308B1; 6,771,124; 6,804,099 and additional patents pending or filed.